

不锈钢带座轴承



Bearing NO.	Bore in	Diam (d) mm	Shape Dimension(mm)								Dynamic load(N)	Statie load(N)	Weight (Kg)
			D	B	C	S	S1	G	ds	F			
SSUC201-8	1/2	/	1.8504	1.2205	0.6693	0.5	0.7205	0.189	37009	0.1614	12800	6650	0.19
SSUC201	/	12	1.8504	1.2205	0.6693	0.5	0.7205	0.189	37009	0.1614	12800	6650	0.2
SSUC202-9	9/16	/	1.8504	1.2205	0.6693	0.5	0.7205	0.189	37009	0.1614	12800	6650	0.19
SSUC202-10	5/8	/	1.8504	1.2205	0.6693	0.5	0.7205	0.189	37009	0.1614	12800	6650	0.19
SSUC202	/	15	1.8504	1.2205	0.6693	0.5	0.7205	0.189	37009	0.1614	12800	6650	0.19
SSUC203-11	11/16	/	47	31	17	12.7	18.3	4.8	M6*1	4.1	12800	6650	0.17
SSUC203	/	17	47	31	17	12.7	18.3	4.8	M6*1	4.1	12800	6650	0.18
SSUC204-12	3/4	/	47	31	17	12.7	18.3	4.8	M6*1	4.1	12800	6650	0.16
SSUC204	/	20	47	31	17	12.7	18.3	4.8	M6*1	4.1	12800	6650	0.16
SSUC205-13	13/16	/	2.0472	1.3426	0.6693	0.563	0.7795	0.1969	37009	0.1614	1400	7850	0.24
SSUC205-14	7/8	/	2.0472	1.3426	0.6693	0.563	0.7795	0.1969	37009	0.1614	1400	7850	0.23
SSUC205-15	15/16	/	2.0472	1.3426	0.6693	0.563	0.7795	0.1969	37009	0.1614	1400	7850	0.21
SSUC205-16	1	/	52	34.1	17	14.3	19.8	5	M6*1	4.1	1400	7850	0.2
SSUC205	/	25	52	34.1	17	14.3	19.8	5	M6*1	4.1	1400	7850	0.2
SSUC206-17	1 1/16	/	2.4409	1.5	0.748	0.626	0.874	0.1969	37009	0.2165	19500	11300	0.33
SSUC206-18	1 1/8	/	2.4409	1.5	0.748	0.626	0.874	0.1969	37009	0.2165	19500	11300	0.34
SSUC206-19	1 3/16	/	2.4409	1.5	0.748	0.626	0.874	0.1969	37009	0.2165	19500	11300	0.32
SSUC206-20	1 1/4	/	62	38.1	19	15.9	22.2	5	M6*1	5.2	19500	11300	0.31
SSUC206	/	30	62	38.1	19	15.9	22.2	5	M6*1	5.2	19500	11300	0.32
SSUC207-20	1 1/4	/	2.8346	1.689	0.7874	0.689	1	0.2756	5/16-24	0.2165	25700	15300	0.54
SSUC207-21	1 5/16	/	2.8346	1.689	0.7874	0.689	1	0.2756	5/16-24	0.2165	25700	15300	0.51
SSUC207-22	1 3/8	/	2.8346	1.689	0.7874	0.689	1	0.2756	5/16-24	0.2165	25700	15300	0.48
SSUC207-23	1 7/16	/	72	42.9	20	17.5	25.4	7	M8*1.0	5.5	25700	15300	0.45
SSUC207	/	35	72	42.9	20	17.5	25.4	7	M8*1.0	5.5	25700	15300	0.48
SSUC208-24	1 1/2	/	3.1496	1.937	0.8268	0.748	1.189	0.315	5/16-24	0.244	29500	18100	0.68

不锈钢带座轴承

SSUC208-25	$\frac{1}{9/16}$	/	/	/	/	/	/	/	/	/	29500	18100	0.65
SSUC208	/	40	80	49.2	21	19	30.2	8	M8*1.0	6.2	29500	18100	0.64
SSUC209-26	$\frac{1}{5/8}$	/	3.3465	1.937	0.8661	0.748	1.189	0.315	5/16-24	0.252	31600	20600	0.78
SSUC209-27	$\frac{1}{11/16}$	/	3.3465	1.937	0.8661	0.748	1.189	0.315	5/16-24	0.252	31600	20600	0.74
SSUC209-28	$\frac{1}{3/4}$	/	85	49.2	22	19	30.2	8	M8*1.0	6.4	31600	20600	0.7